www.se.com
W9 1378085 0511 A15
12 - 2022
© 2022 Schneider Electric - All rights reserved.

Schneider Electric Limited
Stafford Park 5
Telford, TF3 3BL
United Kingdom
www.se.com/uk

UK CA

3P AC TeSys K contactors are grade 2 according to GB 21518.
Maximum power consumption lower than 5.0 VA.
根据GB 21518标准，
三级 TeSys K系列交流接触器能效等级为2级。
产品最大吸持功率低于5.0 VA

Phillips head 'PH' — PH2
Pozidriv head 'PZ' — PZ2
6 mm

mm	mm²	mm²	mm²	mm²	mm²	mm²	mm	C N.m	L mm	Ø mm	L mm
1 x 6,35 2 x 2,8	0,34 … 2,5	0,34…2,5 + 0,34…1,5	0,75…4	0,75…4 + 0,75…4	1,5…4	1,5…4 + 1,5…4	7	1.3	7	3	8

AWG :1 x 18 min, 2 x 14 or 1 x 12 max
规格:1 x 18最小值，2 x 14或1 x 12最大值

Torque 0.8-1.3 N.m (7-12 lb-in)
扭矩:0.8-1.3 N.m(7-12 lb-in)

⚠⚠ DANGER / 危险

HAZARD OF ELECTRIC SHOCK, EXPLOSION, OR ARC FLASH
Disconnect all power before servicing equipment.
Failure to follow these instructions will result in death or serious injury.

电击、爆炸或电弧闪光危险
在此电力设备上进行操作时，请先断开所有电源。
不遵循上述说明将导致人员伤亡。

For motor starting use Schneider Electric TeSys Protect - K overload relays.
电动机起动请使用施耐德电气TeSys保护K系列热过载继电器。

RECYCLABLE

4 x Ø 4 mm (6 UNC)
50 / 1.97 in
35 / 1.38 in

⚠⚠ WARNING / 警告

HAZARD OF FIRE OR ELECTRIC SHOCK (FOR CONTACTOR WITH UL HI-FAULT SHORT CIRCUIT CURRENT RATINGS ONLY)
- The opening of the branch-circuit protective device may be an indication that a fault current has been interrupted.
- To reduce the risk of fire or electric shock, curent-carrying parts and the other components of the controller should be examined and replaced if damaged.

Failure to follow these instructions can result in death, serious injury, or equipment damage.

有火灾或电弧灼伤危险（仅当继电器发生超高故障短路电流时）
- 分支电流保护装置断开可能表明某故障电流已被切断。
- 为减少火灾或电弧烧伤的危险，应经常检查和更换（如损坏）控制器的带电部分及 其它部件。

不遵循上述说明可能导致人员伤亡或设备损坏。

- Surge suppressor
- Limiteur de surtension
- Uberspannungsbegrenzer
- Limitatore di sovratensione
- Limitador de sobretención
- Limitador de sobretensão
- 浪涌抑制器

Schneider Electric Industries SAS
35 Rue Joseph Monier
92506 Rueil Malmaison, France

~ / ⎓

LA4 KE.

⎓

LA4 KC.