

SYSTEM SHIFT BASIC GRID S

WLD+70010WW



See
more

On track luminaire SYSTEM SHIFT BASIC GRID S, with a power of 12 W, high light efficacy 108 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 24° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	12 W	Voltage	48 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	24 °	UGR	<19
Degree of protection (IP)	IP20		

Technical data


Code	WLD+70010WW
Power	12 W
Nominal current	240 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1300 lm (360°)
Luminous flux**	1000 lm (360°)
Lamp efficacy	108 lm/W
Luminous intensity	4500 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	24 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	220x23x42 mm
For use	Inside
Assembly method	NA SZYŃĘ
Application	Inside
Made in	PRC

Related documents



 User manual



 Declaration of Conformity

